

ThistlePro® selector guide

Finish Coat - Performance finish



Product	ThistlePro FastSet Finish	ThistlePro DuraFinish	ThistlePro PureFinish	ThistlePro Magnetic		
Product description	Versatile fast setting finish plaster ideal for most backgrounds. Formulated to guarantee a high quality finish in less time	Versatile and hard wearing plaster ideal for most backgrounds. Proven 60% tougher than standard skims	For use on a wide range of backgrounds. Provides a smooth, high quality surface to internal walls and ceilings	Applied the same as standard plaster with a minimum thickness of 3mm to enable magnetic attraction to any wall. For use on a wide range of backgrounds. It provides a smooth, high quality surface which attracts magnets to internal walls		
Benefits of product	Provides a faster setting finish compared to standard plasters, giving you a guaranteed way to get the job done faster	Excellent resistance to glancing impacts or accidental damage like scratching, gouging or chipping. Damage to small areas does not spread or cause debonding, making repair easier	ThistlePro PureFinish contains ACTIVair technology, designed specifically to improve indoor air quality and decomposes formaldehyde emissions into non-harmful inert compounds, thus eliminating the risk of re-emission	Transform any wall into a surface that attracts magnets, making the ideal display board where what's on show can be endlessly changed. Perfect for children's bedrooms, schools, kitchens and offices		
Finish colour						
Where generally used	Ideal for finishing ceilings and walls, reskims including painted reskims, plasterboard and backing coats	In high traffic areas at home, school or work. Ideal to use with Gyproc Habito and Gyproc DuraLine partitions with extra robustness requirements. Applied to most wall types including plasters and plasterboard	Ideally used in hospitals, schools, children's rooms and family homes where air quality for inhabitants is important. Applied onto most wall types	Perfect for children's bedrooms, living areas and kitchens, in homes as well as schools, offices and meeting rooms		
Preparation advice	For fastest finish, use a single mix for both first and second coat. Use Thistle GypPrime to control suction and Thistle Bond-it for an improved key	Dampen dry undercoats first or where background suction is extremely high, use Thistle GypPrime. Once mixed, leave to sit for 5 mins, then re-mix a final time before applying	Dampen dry undercoats first or where background suction is extremely high, use Thistle GypPrime. Use Thistle Bond-it on moisture resistant boards and flat smooth concrete	Dampen dry undercoats first or where background suction is extremely high, use Thistle GypPrime. Use Thistle Bond-it on moisture resistant boards and flat smooth concrete		
SUCTION	Where to use - background surface:					
	High	Dry undercoats	Y	Y	Y	Y
	↑ ↓	Damp undercoats	Y	Y	Y	Y
		Plasterboard	Y	Y	Y	Y
		Flat smooth concrete	Y	Y	Y	Y
Low	Waterproof or cement-based undercoats	Y	Y	-	-	
APPLICATION	Application:					
	Hand applied	Y	Y	Y	Y	
	Spray applied	-	-	-	-	
	Thickness applied - walls	2mm	2mm	2mm	3-6mm	
	Coverage per bag at 2mm	10m ²	10m ²	10m ²	5m ² (3mm)	
	Water requirement (litres per bag)	11.5	11.5	11.5	8	
SET	Dry set weight at 2mm	2.7kg/m ²	-	2.7kg/m ²	-	
	Minimum setting time*	60 mins	105 mins	90 mins	200 mins	

* Dependent on environmental conditions.